

# Fyresafe™ Sliding Fire Doors

METALBILT DOORS

## Industrial sliding doors rated to protect from fires for up to four hours.

The Fyresafe™ Sliding Fire Doors are designed and constructed to suit each individual client's needs. Best suited for openings where hinged doors are impractical, Fyresafe™ Sliding Fire Doors will protect from fires for up to four hours and provides half an hour insulation.

### OVERVIEW

Tailor designed and constructed to suit the size of opening, each door is fire rated for masonry walls to provide up to -/240/30 FRR.

### APPLICATIONS

Fyresafe™ Sliding Fire Doors are designed to suit many projects including:

- Factories and warehouses
- Record and document stores
- Dangerous goods stores
- Switch rooms
- Hospitals, schools, hotels, shopping centres, carparks and institutions

### SPECIFICATIONS

- Lightweight refracting core.
- Clad in galvanised steel sheeting.
- Capped with steel channels.
- Doors can be single leaf or bi-parting (reducing sidestacking sideroom).
- May be activated by fusible link or by alarm signal.
- Doors can be free to manually slide open and closed or set to 'always open' or 'self-closing' modes (for smaller doors).
- Fire rated for masonry walls to provide up to -/240/30 FRR.
- To achieve fire ratings, walls and floors must be flat and true.

### FINISH

**Standard:** Galvanised Steel

### SIZE

**Maximum width:** 6 metres

**Maximum height:** 5 metres

## Certification

Fire tested and approved to AS 1530.4 and comply with NZS 4520

