ARA MANUFACTURE | METALBILT

Tru-Trac™ Sliding Door System Enquiry Form

Download form to PC before editing

Site Details

Company Name:	Date:
Delivery Address:	
Customer Reference/Order Number:	
Contact Name:	Phone:
Site Photos Provided:	Completed By:

Door Requirement

(See TRU-FOLD Data Sheet for full specification details)

1. On the drawing below, enter the door opening measurements (height and width), as well as the headroom and sideroom measurements. Enter the backspace depth if applicable.

(NB: TRU-TRAC panels are a maximum of 5000mmH x 5000mmW. Maximum door width 20 metres). Door opening height measurement must be accurate as Tru-Trac panels are made to suit the opening height with only 10mm of height adjustment.

	DOOR OPENING HEIGHT		
	DOOR OF	PENING WIDTH = mm	
NB		ED DRAW HOW YOU WOULD LIKE YOUR DOOR PA	NELS TO STACK

Tru-Trac[™] Sliding Door System

Wall Construction: Thickness: mm Door Cladding: Zincalume Steel Colorsteel- colour: NB: Cladding is normally supplied by the other suppliers. Metabilt recommends obtaining door cladding from the same supplier thes clad the building. If the cladding is supplied by Metabilit, the profile may not match the building exactly. Floor Rebate: Height: mm omments / Sketch Out of the diameter of the diamete		°C	Wind speed: For Lee Zones, please co	km/h (Max. 134 km/h) nsult Metalbilt
Door Cladding: Zincalume Steel Colorsteel- colour: NB: Cladding is normally supplied by the other suppliers. Metalbilt recommends obtaining door cladding from the same supplier to has clad the building. If the cladding is supplied by Metalbilt, the profile may not match the building exactly. Floor Rebate: Height: mm	Wall Construction:			
Zincalume Steel Colorsteel- colour: NB: Cladding is normally supplied by the other suppliers. Metalbilt recommends obtaining door cladding from the same supplier thas clad the building. If the cladding is supplied by Metalbilt, the profile may not match the building exactly. Floor Rebate: Height: mm	Thickness:		mm	
Colorsteel- colour: NB: Cladding is normally supplied by the other suppliers. Metalbilt recommends obtaining door cladding from the same supplier thas clad the building. If the cladding is supplied by Metalbilt, the profile may not match the building exactly. Floor Rebate: Height: mm	Door Cladding:			
NB: Cladding is normally supplied by the other suppliers. Metalbilt recommends obtaining door cladding from the same supplier to has clad the building. If the cladding is supplied by Metalbilt, the profile may not match the building exactly. Floor Rebate: Height: mm	Zincalume Steel			
has clad the building. If the cladding is supplied by Metalbilt, the profile may not match the building exactly. Floor Rebate: Height: mm	Colorsteel– colour:			
Height: mm				
	Floor Rebate:			
omments / Sketch	Height:		mm	
	_			
	omments / Sketch			
	omments / Sketch			
	omments / Sketch			
	omments / Sketch			
	omments / Sketch			
	omments / Sketch			
	omments / Sketch		Image: Sector of the sector	
	omments / Sketch			
	omments / Sketch			
	omments / Sketch			
	Imments / Sketch Imments / Imments / Sketch Imments / Imments / Sketch Imments / Imments / Imments Imments <tr< td=""><td></td><td></td><td></td></tr<>			

Proposal Acceptance

If you wish to proceed with this proposal/order and agree with Metalbilt terms of trade, please complete your order number and sign this enquiry form, then scan and return to Metalbilt with your signed proposal. Thank you.

Return this form to us to	Place your order	OR	Request a price
Signature:			
Name:		Da	ite:
Proposal Number:		Or	der Number:

0800 638 252 info.nz@metalbilt.co.nz metalbilt.co.nz